



PATENT

ATTORNEY DOCKET NO.: 041464-5018

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Assistant Commissioner for Patents **Box Patent Application** Washington, D.C. 20231

NEW APPLICATION TRANSMITTAL

Transmitted herewith for filing is the patent application of:

Inventor(s): Tomohiro KAWATA and Kunio MITOBE

For: SPEAKER UNIT

1.		ew application		5.77	
	[X]	Itility	[] Design	[] Plant	
2.	9		h are required for a fill fication including s and act	ing date:	
	_ <u>5</u> 6	Sheets of Figures	[X] FORMAL	[] INFORMAL	drawings containing
			_ , ,	photograph(s), and the HOTOGRAPH(S) AS I	
3.	Combi	Enclosed - and Not Enclosed This application Applicant(s) a		ventors the provisions of 37 C the Patent and Tradem	
4.	Langu [X]	English Non-English This application		cordance with 37 C.F.R otification from the Pate	§1.52(d) and §608.01 ent and Trademark

Office of the time set for filing the verified English translation and the processing fee.

5.	Assign	is attached and Assignment of the invention is to
	[X]	will be filed at a later date
6.		ed Copy eation(s) from which priority is claimed are:

Country	Application No.	Filed
Korea	8-266684	September 17, 1996
		7 2 21 0 11

Certified copy(ies) is/are [X] attached [] will follow

7. Fee Calculation

	C	LAIMS AS FILED		
	Number Filed	Number Extra	at Rate of	Basic Fee Utility\$770.00 Design\$320.00
Total Claims (37 CFR 1.16(c))	3 - 20 =		\$ 22.00 each=	+
Independent Claims (37 CFR 1.16(b))	1 - 3=		\$ 80.00 each=	+
Multiple dependent claim	+			
			SUB-TOTAL =	\$770.00
	Rec	luction by 1/2 for fil	ing by a small entity	- \$
		ГОТ	TAL FILING FEE =	\$770.00

8. Small Entity Statement(s)

[] Verified Statement(s) that this is a filing by a small entity under 37 C.F.R. §1.9 and §1.27 is(are) attached.

O
1
į.
ŝ
11111 11111
T,
Spaik
2 2 2
ű
iz., j

9.	Fee Pa	ayment
	[]	Not Enclosed.
		NO FEE IS BEING PAID BY CHECK OR DEPOSIT ACCOUNT AT THIS
		TIME.
		This application is being filed under the provisions of 37 C.F.R. §1.53(d).
		Applicant(s) await notification from the Patent and Trademark Office of the time
		set for filing the Declaration and paying the filing fees.
		set for fifting the Declaration and paying the fifting fees.
	[X]	Enclosed.
	[A]	A check in the amount of \$770.00 representing the filing fee of \$770.00 is
		enclosed.
		enciosed.
		Except for issue fees payable under 37 C.F.R. §1.18, the Commissioner is hereby
		authorized by this paper to charge any additional fees during the entire pendency
		of this application including fees due under 37 CFR §1.16 and §1.17 which may
		be required, or credit any overpayment to Deposit Account
		13-4520.
10.	Δddit	ional papers enclosed.
10.	LJ	Preliminary Amendment
		1 feminiary Amendment

Please accord an application number and filing date.

Information Disclosure Statement

Form PTO-1449

Citations

[]

Respectfully submitted,

MORĢAN, LĘWIS & BOCKIUS LLP

J. Michael Thesz

Reg. No. 40,354

Dated: September 16, 1997

MORGAN, LEWIS & BOCKIUS LLP 1800 M Street, N.W. Washington, D.C. 20036 (202)467-7000

10

15

20

25

TITLE OF THE INVENTION

Speaker Unit

BACKGROUND OF THE INVENTION

The present invention relates to a speaker unit, in particular to a speaker unit which is thin in thickness and has an elliptical shape.

There has been known a thin type speaker unit which is for use in a television set and whose vibrating diaphragm is usually formed into an elliptical shape. On the other hand, it is usually required that a magnetic circuit of a speaker unit be formed in a manner such that it can provide a uniform magnetic flux to the surface of a cylindrical voice coil. Accordingly, it is often required that a top plate and a permanent magnet each having a circular doughnut shape be used so that the whole magnetic circuit has a cylindrical shape.

In fact, a thin type speaker unit usually has a magnetic circuit whose outer diameter is equal to or smaller than a width in a short axis direction of a frame structure which supports a vibrating diaphragm. In this way, a speaker unit as a whole may be made smaller, thus meeting with a requirement of making a compact speaker unit.

However, in a thin type speaker unit as above related, since a magnetic circuit has to be made small in size due to a restriction caused by a width in the short axis direction of a vibrating diaphragm, the magnetic flux to be applied to the

10

15

20

25

surface of a voice coil will have a low density, resulting in a problem that the speaker unit has only a low sensitivity.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide an improved speaker unit so as to solve the above-mentioned problem peculiar to the above-mentioned prior art.

According to the present invention, there is provided a speaker unit comprising: an elliptical vibrating diaphragm; a cylindrical voice coil secured at one end thereof on the the elliptical vibrating diaphragm; a frame center of structure for movably supporting the vibrating diaphragm, said frame structure being formed into a rectangular or elliptical shape and having a through hole in the center thereof; a magnetic circuit formed by (1) a top plate having a rectangular shape and having a through hole in the center thereof, (2) a plate-shaped magnet having a rectangular shape and having a through hole in the center thereof, (3) a back plate having a rectangular shape and having an upright pole on In this speaker unit, the top plate, the the center thereof. plate-shaped magnet and the back plate each has a width which is narrower than that of the frame structure in its shorter axis.

According to one aspect of the present invention, the frame structure, the top plate, the plate-shaped magnet and the back plate are arranged in parallel relation with one

another.

The above objects and features of the present invention will become more understood from the following description with reference to the accompanying drawings.

5

BRIEF DESCRIPTION OF DRAWINGS

Fig. 1 is an exploded perspective view showing a series of elements for forming a magnetic circuit for use in a speaker unit according to the present invention.

10 Fig. 2 is an end view showing a speaker unit of the present invention in its shorter axis.

Fig. 3 is a side view showing a speaker unit of the present invention in its longer axis.

Fig. 4 is a perspective view showing a frame for use in the speaker unit of the present invention.

Fig. 5a is a front view showing a television set in which the speaker unit of the present invention is applied.

Fig. 5b is a top plane view showing the television set of Fig. 5a.

20

25

15

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Fig. 1, reference numeral 1 represents a rectangular top plate which is made of a magnetic material and has a center hole 1a. Reference numeral 2 represents a rectangular plate-shaped magnet having a center hole 2a. Reference numeral 3 represents a back plate 3 made of a

10

15

20

25

magnetic material and having a center pole 3a smaller in diameter than hole 1a. Reference numeral 4 represents another plate-shaped magnet having a central hole 4a. The magnet 4 is used to cancel leaked magnetic flux from the magnet 2. Reference numeral 5 represents a case made of a magnetic material for receiving the top plate 1, the magnet 2, the back plate 3 and the magnet 4.

In use, the top plate 1 serves as a lid to cooperate with the case 5 so as to receive the magnet 2, the back plate 3 and the magnet 4. In this way, magnetic flux possibly leaked from the magnet 2 will be effectively blocked so as to be confined within the case 5.

Referring to Figs. 2 - 4, reference numeral 6 represents a rectangular parallelepiped frame structure which is used to movably support an elliptical vibrating diaphragm (not shown). As shown in Fig. 4, the frame structure 6 is formed with a elliptical recess portion 6a for receiving an elliptical vibrating diaphragm. Further, a center hole 6b, which has the same diameter as that of the center hole 1a of the top plate 1, is formed on the bottom of the elliptical recess portion 6a.

Referring again to Figs. 1 and 3, the frame structure 6, the top plate 1, the magnet 2, the back plate 3 and the magnet 4 are assembled together with their longer axes arranged in parallel with one another.

Referring to Fig. 3, the frame structure 6 is the longest

in length.

5

10

15

20

25

After being assembled into a condition as shown in Fig. 3, the hole la of the top plate 1, the hole 2a of the magnet 2, the hole 4a of the magnet 4 and the hole 6a of the frame structure 6 are all aligned in a vertical line so that the centers of these holes become coincident with one another, thereby permitting the center pole 3a of the back plate 3 to be inserted through all these holes. In this way, a magnetic circuit is formed by virtue of the top plate 1, the A magnetic gap is formed in magnet 2 and the back plate 3. an annular space formed between the inner wall of the hole la and the surface of the center pole 3a. A cylindrical voice coil (not shown) having one end thereof fixed at the center of a vibrating diaphragm (not shown) is inserted in the annular space.

Referring to Fig. 2, the frame structure 6 has a larger width than the top plate 1, the magnet 2 and the back plate 3. As compared with a conventional speaker unit where a doughnut-shaped magnet is used to form a cylindrical magnetic circuit, since the magnet 2 in the present invention has a larger volume than that in prior art, the magnetic flux to be applied to the voice coil will have a larger density. Further, since the magnetic circuit in the present invention is shorter in its longer axis and narrower in its shorter axis than the frame structure 6, a cabinet (into which the speaker unit is to be received) is required to have only a small

10

15

20

25

volume which may be the same as that of a cabinet for a conventional speaker unit (having a cylindrical magnetic circuit), but achieving a higher sensitivity than a conventional speaker unit.

Fig. 5a is a front view and Fig. 5b is a top plane view, showing an example where the speaker unit of the present invention is installed in a television set. As shown in Fig. 5a, the television set comprises a frame 10 holding a display 30. Provided on either side of the display 30 is a speaker unit 20 manufactured in accordance with the present invention. It has been found that the speaker unit of the present invention is particularly suitable for use in a television set in which there is only an elongate narrow space for installing a speaker unit.

It is understood from the above description that with the use of the present invention, the magnet of a speaker unit is allowed to be made larger than prior art so that the magnetic flux to be applied to the voice coil will have a higher density than prior art, thereby enabling a speaker unit to obtain an improved sensitivity.

Further, since the magnetic circuit in the present invention is shorter in its longer axis and narrower in its shorter axis than a frame structure for supporting a vibrating diaphragm, a cabinet (into which the speaker unit is to be received) is required to have only a small volume which may be the same as that of a cabinet for a conventional speaker unit

(having a cylindrical magnetic circuit), but achieving a higher sensitivity than a conventional speaker unit.

While the presently preferred embodiments of the this invention have been shown and described above, it is to be understood that these disclosures are for the purpose of illustration and that various changes and modifications may be made without departing from the scope of the invention as set forth in the appended claims.

WHAT IS CLAIMED IS:

1. A speaker unit comprising:

an elliptical vibrating diaphragm;

a cylindrical voice coil secured at one end thereof on the center of the elliptical vibrating diaphragm;

a frame structure for movably supporting the vibrating diaphragm, said frame structure being formed into a rectangular or elliptical shape and having a through hole in the center thereof;

a magnetic circuit formed by (1) a top plate having a rectangular shape and having a through hole in the center thereof, (2) a plate-shaped magnet having a rectangular shape and having a through hole in the center thereof, (3) a back plate having a rectangular shape and having an upright pole on the center thereof:

wherein the top plate, the plate-shaped magnet and the back plate each has a width which is narrower than that of the frame structure in its shorter axis.

- 2. The speaker unit according to claim 1, wherein the frame structure, the top plate, the plate-shaped magnet and the back plate are arranged in parallel relation with one another.
- 3. The speaker unit according to claim 1 is installed on either side of a television display on a television set.

Speaker Unit

Abstract of the Disclosure

provided a speaker unit comprising: There elliptical vibrating diaphragm; a cylindrical voice coil secured at one end thereof on the center of the elliptical vibrating diaphragm; a frame structure for movably supporting the vibrating diaphragm, said frame structure being formed into a rectangular or elliptical shape and having a through hole in the center thereof; a magnetic circuit formed by (1) a top plate having a rectangular shape and having a through hole in the center thereof, (2) a plate-shaped magnet having a rectangular shape and having a through hole in the center thereof, (3) a back plate having a rectangular shape and having an upright pole on the center thereof. In this speaker unit, the top plate, the plate-shaped magnet and the back plate each has a width which is narrower than that of the frame structure in its shorter axis.

COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY

		U.S. DEF	PARTMENT OF COMMERCE Patent and Trademark Office
		ATTO	RNEY DOCKET NO.:
As a below named inventor, I he	ereby declare that:		
My residence, post office address	s and citizenship are as stated be	low next to my name,	
I believe I am the original, first plural names are listed below) o	and sole inventor (if only one nar f the subject matter which is clain	ne is listed below) or an original med and for which a patent is so	, first and joint inventor (if aght on the invention entitled:
87	KER UNIT"		
the specification of which:			
is attached hereto; or			
was filed as United States applicapplicable); or	ation Serial Noon	and was amende	ed on(if
was filed as PCT international a	oplication Numbero	n and was amen	ded under PCT Article 19
]]]	аррисанс).		
I hereby state that I have review	ed and understand the contents o	of the above-identified enecification	n including the claims as
amended by any amendment refe	erred to above.	r the above-identified specification	n, including the claims, as
acknowledge the duty to disclo	se to the IIS Datent and Tradem	ork Office information which is	
claims presented in this applicati	on in accordance with Title 37, C	ode of Federal Regulations, §1.5	6(a).
1			
I hereby claim foreign priority be inventor's certificate or of any Po	enefits under Title 35, United State CT international application(s) de	tes Code, §119 of any foreign appropriation at least one country of	plication(s) for patent or
America listed below and have a	lso identified below any foreign a	pplication(s) for patent or invent	or's certificate or any PCT
international application(s) desig subject matter having a filing dat	nating at least one country other e before that of the application(s)	than the United States of Americ of which priority is claimed:	a filed by me on the same
		,	
PRIOR FOREIGN/PO	CT APPLICATION(S) AND AN	NY PRIORITY CLAIMS UND	DER 35 U.S.C. ¶119:
COUNTRY (if PCT, indicate PCT)	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 U.S.C ¶119
Japan	8-266684	17/9/1996	[X] Yes [] No
			[] Yes [] No
			[] Yes [] No
			[] Yes [] No

Combined Declaration	For Patent Application and Power of Attorney - (Continued)
(includes Reference to	PCT International Applications)

ATTORNEY DOCKET NO.:

I hereby claim the benefit under Title 35, United States Code, ¶120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, ¶112, I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to the patentability of claims presented in this application in accordance with Title 37, Code of Federal Regulations, ¶1.56(a) which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application:

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. ¶120:

U.S. APPLICATIONS			STATUS (Check One)		
U.S. APPLICATION NO. U.S. FILING DATE			PATENTED	PENDING	ABANDONED
					·
					·
100 A	<u></u>				
PCT APPLICATIONS DESIGNATING THE U.S.				STATUS (Check On	e)
PCT APPLN. NO.	PCT FILING DATE	U.S. SERIAL NO.	PATENTED	PENDING	ABANDONED

POWER OF ATTORNEY: as a named inventor, I hereby appoint the following attorneys to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

MORGAN, LEWIS & BOCKIUS

Robert J. Gaybrick, Reg. No. 27,890; John G. Smith, Reg. No. 33,818; Song K. Jung, Reg. No. 35,210; Michele Schafer, Reg. No. 34,717; Matthew T. Bailey, Reg. No. 33,829; Bruce G. Bernstein, Reg. No. 34,550;

Send Correspondence To:

TI

MORGAN, LEWIS & BOCKIUS 1800 M Street, N.W.

Washington, D.C. 20036-5869

Direct Telephone Calls To: (name and telephone number)

Robert J. Gaybrick (202) 467-7501

A CONTRACTOR OF THE CONTRACTOR		
Combined Declaration For (includes Reference to PCT	Patent Application and Power of Attorney - (Continued) International Applications) ATTORNEY DOC	KET NO.:
made on informa the knowledge th both, under Secti	that all statements made herein of my own knowledge are true and that all stater tion and belief are believed to be true; and further that these statements were m at willful false statements and the like so made are punishable by fine or imprison 1001 of Title 18 of the United States Code, and that such willful false statemed lidity of the application or any patent issuing thereon.	ade with nment, or
FULL NAME OF SOLE OR FIRST INVENTOR	Tomohiro KAWATA	
RESIDENCE & CITIZENSHIP	CITY AND STATE OR CITY AND FOREIGN COUNTRY Yamagata-ken, Japan	COUNTRY OF CITIZENSHIP Japan
POST OFFICE ADDRESS	c/o Tohoku Pioneer Electronic Corporation 1105 Aza Nikko, Ooaza Kunomoto, Tendo-shi, Yam 994 Japan	agata-ken
FIRST OR SOLE INVENT	-	DATE July 9, 1997
FULL NAME OF SECOND INVENTOR	Kunio MITOBE	
RESIDENCE & ETIZENSHIP	CITY AND STATE OR CITY AND FOREIGN COUNTRY Yamagata-ken, Japan	COUNTRY OF CITIZENSHIP Japan
POST OFFICE ADDRESS	c/o Tohoku Pioneer Electronic Corporation 1105 Aza Nikko, Ooaza Kunomoto, Tendo-shi, Yam 994 Japan	agata-ken
SECOND INVENTOR'S	SIGNATURE pluno Siloto	DATE July 9,1997
FULL NAME OF THIRD INVENTOR		
RESIDENCE &	CITY AND STATE OR CITY AND FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP

Listing of Inventors Continued on attached page(s) [] Yes	[] No
--	-------	--------

DATE

THIRD INVENTOR'S SIGNATURE

CITIZENSHIP

POST OFFICE ADDRESS

FIG.1





FIG.2



(gp \






FIG.5 a




FIG.5 b

